


Product data sheet

Specifications



Asfora -1pole pushbutton-10A screwless, locator light, bell symbol, wh wo frame

EPH1770121

⚠ Discontinued on: Jun 30, 2023

⚠ Discontinued

Main

Range	Asfora
Product or component type	Push-button
Device presentation	Mechanism with fixing frame
Number of rocker	1
Colour tint	White
Type of packing	Flow-pack

Complementary

Device mounting	Flush
Local signalling	LED
Power range	2300 W
Rated current	10 A at 250 V AC
Number of cables	2 cable(s) 2.5 mm ²
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13.0 mm
Material	ABS (acrylonitrile butadiene-styrene)
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Screws or claws 51...70 mm
Connections - terminals	Screwless terminals
Marking	Bell symbol
Width	71 mm
Height	71 mm
Depth	43.0 mm
Projecting depth	15 mm
Net weight	0.0608 kg

Environment

Standards	IEC 60669-1
-----------	-------------

Product certifications	TSE VDE NF
Quality labels	CE UKR
IP degree of protection	IP20
Ambient air temperature for operation	-5...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.1 cm
Package 1 Width	7.1 cm
Package 1 Length	4.3 cm
Package 1 Weight	61.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	9.1 cm
Package 2 Width	18.5 cm
Package 2 Length	27.5 cm
Package 2 Weight	738.0 g
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Height	30.0 cm
Package 3 Width	40.0 cm
Package 3 Length	60.0 cm
Package 3 Weight	9.52 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

SCIP Number **C6de3800-7220-4403-a6a2-26e1f05e3f4b**

China RoHS Regulation [China RoHS declaration](#)

Use Again

Repack and remanufacture

Circularity Profile **No need of specific recycling operations**