

Product data sheet

Specifications



Asfora - single socket outlet with side earth - 16A white

EPH2900121

Main

| | |
|----------------------------|---------------|
| Range | Asfora |
| Product or component type | Socket-outlet |
| Socket number | 1 |
| Outlet poles configuration | 2P + E |
| Colour tint | White |
| Type of packing | Flow-pack |

Complementary

| | |
|-----------------------------|---|
| Device presentation | Complete product |
| Device mounting | Flush |
| Fixing mode | Screws or claws51...69 mm |
| Outlet standard | CEE 7/3 |
| Outlet standard deviation | Schuko |
| Outlet standard description | Side earth |
| Power range | 3680 W |
| Rated current | 16 A at 250 V AC |
| Surface finish | Glossy |
| Material | ABS (acrylonitrile butadiene-styrene): cover frame ABS + PC: central plate |
| Wire stripping length | 13.0 mm |
| Conductor material | Copper |
| Connections - terminals | Lift terminals |
| Number of cables | 2 cable(s) 2.5 mm ² |
| Cable stiffness | Flexible Rigid Solid stranded |
| Quantity per set | 1 |
| IP degree of protection | IP20 |
| Projecting depth | 10 mm |
| Width | 83 mm |
| Height | 83 mm |
| Depth | 42 mm |
| Net weight | 0.08 kg |

Environment

| | |
|------------------------|-------------|
| Standards | IEC 60884-1 |
| Product certifications | TSE VDE |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.000 cm |
| Package 1 Width | 8.500 cm |
| Package 1 Length | 8.500 cm |
| Package 1 Weight | 79.300 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 9.500 cm |
| Package 2 Width | 18.500 cm |
| Package 2 Length | 27.500 cm |
| Package 2 Weight | 870.000 g |
| Unit Type of Package 3 | S04 |
| Number of Units in Package 3 | 120 |
| Package 3 Height | 30.000 cm |
| Package 3 Width | 40.000 cm |
| Package 3 Length | 60.000 cm |
| Package 3 Weight | 11.041 kg |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 1

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile No need of specific recycling operations

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back No