

# Product data sheet

Specifications



## Asfora, SAT socket ending, 1dB, steel

EPH3700162

### Main

|                                      |  |
|--------------------------------------|--|
| Range                                | Asfora   |
| Product or component type            | SAT socket   |
| Device presentation                  | Mechanism with fixing frame  |
| TV socket type                       | End-of-line (terminal socket)  |
| Wiring device additional information | For parallel distribution systems<br>For series distribution systems |
| Type of packing                      | Flow-pack  |

### Complementary

|                         |  |
|-------------------------|--|
| Device mounting         | Flush  |
| Fixing mode             | Claws51...80 mm                                      |
| Socket number           | 1  |
| SAT connector           | F type   |
| Attenuation             | 1 dB   |
| Colour tint             | Steel  |
| Surface finish          | Painted  |
| Material                | ABS (acrylonitrile butadiene-styrene): central plate |
| DC current flow         | In SAT socket  |
| Number per line         | 1  |
| Connections - terminals | Screwless terminals                                  |
| Conductor material      | Copper   |
| Height                  | 71 mm  |
| Width                   | 71 mm  |
| Depth                   | 42 mm  |
| Projecting depth        | 13 mm  |
| Net weight              | 0.075 kg   |
| IP degree of protection | IP20   |

### Environment

|                |    |
|----------------|----|
| Quality labels | CE |
|----------------|----|

### Packing Units

|                                     |           |
|-------------------------------------|-----------|
| <b>Unit Type of Package 1</b>       | PCE       |
| <b>Number of Units in Package 1</b> | 1         |
| <b>Package 1 Height</b>             | 3.5 cm    |
| <b>Package 1 Width</b>              | 7.3 cm    |
| <b>Package 1 Length</b>             | 7.3 cm    |
| <b>Package 1 Weight</b>             | 75.0 g    |
| <b>Unit Type of Package 2</b>       | BB1       |
| <b>Number of Units in Package 2</b> | 10        |
| <b>Package 2 Height</b>             | 9.4 cm    |
| <b>Package 2 Width</b>              | 18.5 cm   |
| <b>Package 2 Length</b>             | 27.5 cm   |
| <b>Package 2 Weight</b>             | 828.0 g   |
| <b>Unit Type of Package 3</b>       | S04       |
| <b>Number of Units in Package 3</b> | 120       |
| <b>Package 3 Height</b>             | 30.0 cm   |
| <b>Package 3 Width</b>              | 40.0 cm   |
| <b>Package 3 Length</b>             | 60.0 cm   |
| <b>Package 3 Weight</b>             | 10.639 kg |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

[EU RoHS Directive](#)

Compliant

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

## Use Again

### Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)

WEEE

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back

No