

# Product data sheet

Specifications



## Unica Top/Class - 1 S.O. (lid) - 2P+E, shutters, DE - 2 m - graphite

MGU3.037.12TA

⚠ Discontinued on: Sep 30, 2023

⚠ Discontinued

### Main

|                             |                         |
|-----------------------------|-------------------------|
| Range                       | Unica                   |
| Product or component type   | Socket-outlet           |
| Aesthetic name              | Unica Top - Unica Class |
| Device presentation         | Mechanism               |
| Device mounting             | Flush                   |
| Socket number               | 1                       |
| Outlet poles configuration  | 2P + E                  |
| Outlet standard deviation   | Schuko                  |
| Outlet standard description | Side earth              |
| Rated current               | 16 A                    |

### Complementary

|                                |   |
|--------------------------------|---|
| Device application             | Power supply  |
| Cover type                     | Hinged cover<br>With shutter  |
| [Ue] rated operational voltage | 250 V   |
| Network type                   | AC  |
| Network frequency              | 50/60 Hz  |
| Number of modules              | 2 modules   |
| Fixing mode                    | Clip-in   |
| Colour tint                    | Graphite  |
| Connections - terminals        | Screw terminals   |
| Cable cross section            | 0...4 mm <sup>2</sup> - cable stiffness: flexible<br>0...4 mm <sup>2</sup> - cable stiffness: rigid |
| Minimum load breaking capacity | 100 operations 1.25 In and 1.1 Un, cos phi = 0.6  |
| Electrical durability          | 10000 cycles, cos phi = 0.8   |
| Insulation resistance          | > 5 MOhm at 500 V   |
| Dielectric strength            | 2000 V  |
| Material                       | ASA + PC: mechanism cover   |
| Quantity per set               | Set of 1 blister  |
| Product certifications         | FR.ME63.B02375 AC<br>14.10.01/5433  |

|                 |           |
|-----------------|-----------|
| Embedding depth | 30 mm     |
| Depth           | 40 mm     |
| Width           | 45 mm     |
| Height          | 45 mm     |
| Net weight      | 0.0408 kg |

## Environment

|                                       |   |
|---------------------------------------|---|
| Ambient air temperature for operation | 15...30 °C  |
| Ambient air temperature for storage   | 0...35 °C   |
| IK degree of protection               | IK01  |
| IP degree of protection               | IP20  |
| Environmental characteristic          | Alcohol<br>Window-cleaning fluid<br>Liquid soap<br>Bleach<br>Acetone<br>Oil<br>UV resistant<br>Petrol |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 4.5 cm   |
| Package 1 Width              | 4.6 cm   |
| Package 1 Length             | 4.6 cm   |
| Package 1 Weight             | 40 g     |
| Unit Type of Package 2       | BB1      |
| Number of Units in Package 2 | 10       |
| Package 2 Height             | 12.7 cm  |
| Package 2 Width              | 12.4 cm  |
| Package 2 Length             | 18.5 cm  |
| Package 2 Weight             | 463 g    |
| Unit Type of Package 3       | S03      |
| Number of Units in Package 3 | 80       |
| Package 3 Height             | 30 cm    |
| Package 3 Width              | 30 cm    |
| Package 3 Length             | 40 cm    |
| Package 3 Weight             | 4.192 kg |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

## Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

China RoHS Regulation

[China RoHS declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile

No need of specific recycling operations

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins